# FB20 Longmaterial Box fawic.nl PackagingSystems

# FB20 now also specially for long material

The FB20 Longmaterial Box protects your goods in the best possible manner during transportation. The box consists of strong sandwich panels and a sturdy panel-locking system.

This rigid box makes it possible for you to transport long objects quickly and easily. And in large quantities.

The FB20 system is also dust and watertight.

# Including a unique loading and unloading system

The Longmaterial Box can be supplied with a unique loading and unloading system. This makes the box easy to raise and to move around, without requiring a hand truck or a fork-lift truck. Which means that now you can quickly and easily transport long – and previously awkward – materials! The system itself takes up scarcely any space and is also lightweight. The photos show how the box can be raised and moved around in the practical situation.

# Lightweight and patented

Like all the Fawic transport boxes, the Longmaterial Box is fitted with our patented FB20 locking system. This links the panels seamlessly together. High-quality, lightweight panels, offering excellent insulation and protection. The construction is stable, is resistant to the weather and guarantees safe transportation.

# Rapid and applicable everywhere

The FB20 Longmaterial Box is ideal for long articles and products, including vulnerable materials. The handy locking system means that you can assemble and disassemble the panels very quickly. And thanks to the loading and unloading system, this box is suitable for spare parts and end-products from the entire assembly line.

### Design and dimensions

The table gives the standard sizes of the FB20 Longmaterial Box.

The separate panels and the Fawic locking system mean, of course, that you can make Boxes to your own specifications. See below for further information and technical specifications.







Dimensions	
External dimensions (I x b x h)	Internal dimensions (I x b x h)
400 x 400 x up to 6000 mm	395 x 395 x up to 6000 mm (minus approx. 50 mm)
500 x 500 x up to 6000 mm	495 x 495 x up to 6000 mm (minus approx. 50 mm)
600 x 600 x up to 6000 mm	595 x 595 x up to 6000 mm (minus approx. 50 mm)
700 x 700 x up to 6000 mm	695 x 695 x up to 6000 mm (minus approx. 50 mm)
800 x 800 x up to 6000 mm	795 x 795 x up to 6000 mm (minus approx. 50 mm)
The first of the state of the s	H . 10 1 PG 1 1 1

Height is exclusive of height required for pallet wagon and fork-lift blade Other dimensions available on request

### Design

Collapsible or non-collapsible
With or without hinge
Material: Sandwich panel or PR

Material: Sandwich panel or PP channel plating

# Technical specifications

Panel thickness: up to 20 mm • Dimensions: product-specific •

Load-bearing capacity of locks: approx. 275 kg each • Form-fit locking system •

Protection against dust and splash water •

- Penetration resistance depends on panel
- Goods can be fixed in place
- Can be equipped with: lifting rings, handles, document holder, buffer ring



Fawic BV Twentepoort West 49 7609 RD Almelo The Netherlands

T +31(0)546 767 250 F +31(0)546 767 259

info@fawic.nl



fawic.nl